

LIVOS for OSB

OSB boards in the interior

In the last years OSB boards has become increasingly popular for interior fittings. Often they are used for visible surfaces such as floors, walls and ceilings.

The popularity of OSB has many reasons: They are durable, easy to process and moisture resistant. And unlike wooden fiberboards OSB is characterized by a visually appealing surface, where the raw material timber can still be clearly seen.

In contrast to fiberboards OSB boards consists of relatively large (about 2.0 * 9.5 cm) chips (strands), which are aligned (oriented) in three layers in the composite and are glued together.

OSB has always a slightly uneven surface. Therefore, the preliminary sanding can only smooth, not level. It should not be done with high pressure, so that no chips taken out of OSB composite. The first sanding is performed with 150 grain, the second with 180 grain paper. Between the individual applications an intermediate sanding should be made with 240 grain to smooth standing wood fibers again.

Choose for your OSB surface environmentally friendly and health compatible products.

On the backside you will find a list of suitable products.

For more information, please contact your **LIVOS dealer** or **LIVOS** directly. You can also use our website at www.livos.de and our hotline +49 (0) 5825 - 88 30.

Product selection with some examples

Application Range	Initial treatment	Coatings	After Treatment	Coatings	Result
OSB for walls and ceilings	KUNOS-Natural Oil Sealer No. 244 in different colors	1	KUNOS-Natural Oil Sealer No. 244	3	Colorful design and water-resistant coating
	ARDVOS-Universal Wood Oil No. 266	1	ARDVOS-Universal Wood Oil No. 266	2 - 3	Impregnation and honey toning final treatment
OSB for floors	KUNOS-Natural Oil Sealer No. 244 colored or clear	1	KUNOS-Natural Oil Sealer No. 244 -002, clear or KUNOS-Natural Floor Sealer No. 242	2 - 3	Water resistant, transparent impregnation and final treatment
Cleaning and care	TRENA-pH-Neutral Cleaner No. 556				For weekly cleaning
	GLANOS-Natural Liquid Wax Cleaner No. 559				For monthly care.
Refreshment	KUNOS-Floor Maintenance No. 1862 or KUNOS-Maintenance No. 1893 or product used for initial treatment				To refresh heavily used areas

Pollutants from synthetic paints pollute our air and often lead to diseases of the immune system and allergic reactions. Therefore, healthy interiors require the use of healthy products.

LIVOS offers as the first industrial manufacturer of paints and varnishes made from natural ingredients such products - thus combining more than 38 years of high technical quality with an impressive visual impact, health and environmental protection for the consumer.

All products are tested according to DIN EN 71 regarding heavy metal migration and approved for schools and kindergartens. Your **LIVOS** dealer or the service team at the factory provides instructions for the usage.

Please also note the technical data sheets for the individual products.