

STOPPA

Airtight plugs for conduits



Technical information:

Characteristic	Value
Material	Thermoplastic elastomer (TPE)
Temperature resistance	-10°C to +90°C
Application temperature	> -10°C
Conduit diameter	16 to 40 mm
Colour	blue

Applications:

The sealing plugs, pro clima STOPPA, provide a quick and durable, secure airtight installation of cables in conduits in accordance with DIN 4108-7. Conduit sleeves (see pro clima ROFLEX 20 or ROFLEX 20 multi) are available for an airtight connection of the conduits to the vapour retarder and airtightness membrane.

Delivery forms:

Product name	Mat. No.	EAN	for diameter	PU
STOPPA 16	12945	4026639129451	16 mm (E-06)	20
STOPPA 16	12946	4026639129468	16 mm (E-06)	100
STOPPA 20	12947	4026639129475	20 mm (E-07)	20
STOPPA 20	12948	4026639129482	20 mm (E-07)	100
STOPPA 25	12949	4026639129499	25 mm (E-08)	20
STOPPA 25	12950	4026639129505	25 mm (E-08)	100
STOPPA 32	12951	4026639129512	32 mm (E-09)	20
STOPPA 32	12952	4026639129529	32 mm (E-09)	100
STOPPA 40	12953	4026639129536	40 mm (E-10)	20
STOPPA 40	12954	4026639129543	40 mm (E-10)	100

Features/advantages:

- ✓ Quick and easy airtight sealing in accordance with DIN 4108-7, SIA 180 and Austrian standard B8110-2
- ✓ Flexible press-out circular plug seals around cables of various diameters
- ✓ Easy to pierce with nails or cartridge nozzles
- ✓ Multilayered sealing ribs ensure optimum connection to profiled pipes
- ✓ Can be used for more than one cable
- ✓ Can be removed at a later date

The information provided here is based on practical experience and the current state of knowledge. We reserve the right to make changes to the recommendations given or to make alterations due to technical developments and associated improvements in the quality of our products. We would be happy to inform you of the current technical state of the art at the time you use our products.

