



Technical data:

Characteristic	Value
Release paper	Foil
Temperature resistance	Long-term -20°C to +80°C
Application temperature	+5°C to +35°C
Thickness	1.0 mm
Colour	Black
Storage	Cool and dry

Applications:

As nail sealing tape on the underside of a lath on inclined roofs. TESCON NAiDEC is designed with use for temporary roof coverings as recommended by pro clima.

Delivery forms:

Mat. No.	EAN	Length	Width	PU	PU/Pallet
11737	4026639117373	20 m	5 cm	6	96
11943	4026639119438	20 m	5 cm	24 Big Pack *	24

* Big Pack only available by the box!

Surfaces:

Before bonding, the substrate surface should be brushed clean with a broom or wiped with a cloth. Bonding to frozen surfaces is not possible. The substrate material must be free from water-repellent substances (e.g. grease or silicone). The substrate onto which the tape is applied should be load bearing and stable. Durable nail-tightness is achieved with all pro clima outdoor membranes (sarking membranes or wall lining membranes), sarking membranes and roof lining membranes made from polypropylene and polyester as well as with MDF and softwood fibre sub-roof panels. The best results for the safety of the structure can be achieved on high-quality substrates. The applicator is responsible for checking the suitability of the substrate. Adhesion tests are recommended.

Features/advantages:

- ✓ Liquid butyl adhesive which penetrates deep into the structure
- ✓ Suitable for temporary roof coverings as specified in the pro clima product data sheets

The information provided here is based on practical experience and the current state of knowledge. We reserve the right to make changes to the recommendations given or to make alterations due to technical developments and associated improvements in the quality of our products. We would be happy to inform you of the current technical state of the art at the time you use our products.