

CONTEGA SOLIDO SL

Full-surface adhesive sealing tape for exterior use that can be plastered over, with vapour-retarding properties



Technical data

		Substance
Backing		PP backing fleece, PP copolymer special membrane
Adhesive		waterproof SOLID adhesive
Release film		silicone-coated PE sheet

Attribute	Regulation	Value
Colour		white
sd-value	BS EN 1931	2.8 m
Exposure time		3 months
Can be plastered over		yes
IFT tested (DE-Rosenheim)	MO-01/1:2007-01	yes
Application temperature		above -10 °C / 14 °F
Temperature resistance		permanent -40 °C to +90 °C
Storage		cool and dry

Area of application

The CONTEGA SOLIDO SL joint adhesive tape, which is full-surface adhesive and can be plastered over, ensures interior airtight and vapour-retarding sealing of windows and doors to adjacent building components made of wood and mineral subsurfaces such as concrete and sand-lime brick.

The modified waterproof SOLID adhesive ensures quick and permanent joints with the subsurface.

The stuck joint is immediately airtight and can be subjected to loading. The fleece can easily be plastered over in accordance with our application guide.

Advantages

- ✓ Full-surface adhesive, the joint is immediately airtight and can be subjected to loading
- ✓ Extremely strong adhesion on mineral subsurfaces too thanks to modified waterproof SOLID adhesive
- ✓ Can be plastered over
- ✓ Tape for joints on or under window frames
- ✓ Easy to apply

The information provided here is based on practical experience and the current state of knowledge. We reserve the right to make changes to the recommended designs and processing or to make alterations due to technical developments and associated improvements in the quality of our products. We would be happy to inform you of the current technical state of the art at the time you use our products.



Substrates

Before sticking, subsurfaces should be brushed off or wiped clean with a cloth. Uneven mineral subsurfaces may need to be levelled with a smooth finish.

Adhesion to frozen surfaces is not possible. There must be no water-repellent substances (e.g. grease or silicone) on materials to be bonded. Subsurfaces must be sufficiently dry and have sufficient load-bearing capacity.

Permanent adhesion is achieved on all pro clima interior membranes (vapour retarder and airtight membranes) and PE, PA, PP and aluminium sheeting for the creation of airtightness.

Adhesion can be carried out on planed and painted wood, hard plastics, hard wood-based panels (chipboard, OSB and plywood panels) and on mineral subsurfaces such as concrete and sand-lime brick.

The best results in terms of structural stability are obtained on high-quality subsurfaces. It is your responsibility to check the suitability of the subsurface; adhesion tests are recommended in certain cases.

Pretreatment with TESCON PRIMER RP is recommended in the case of subsurfaces with insufficient load-bearing capacity.

General conditions

The bonds should not be subjected to tensile forces under normal conditions.

Press the adhesive tapes firmly to secure them, taking care to ensure that there is sufficient resistance pressure behind them.

Airtight seals can only be achieved if the sealing tape is installed free of folds and breaks. Ventilate regularly and systematically to prevent build-up of excessive humidity. Use a dryer if necessary.

The information provided here is based on practical experience and the current state of knowledge. We reserve the right to make changes to the recommended designs and processing or to make alterations due to technical developments and associated improvements in the quality of our products. We would be happy to inform you of the current technical state of the art at the time you use our products.



sales: 01793 847 444
email: info@ecomerchant.co.uk
web: www.ecomerchant.co.uk

