



Application of Livos oils to timber decking

Alis decking oil #579 is a water resistant and an open pored oil for the treatment and care of decking, wooden facades, exterior furniture and other exterior timbers. It dries quickly and refreshes wooded surfaces. It does not chip, flake or require re-sanding to rejuvenate. Oiling of decks should be carried out in the dryer months to ensure timber is completely dry. Avoid winter application whenever possible

PREPARATION

The surface must be absorbent, clean and dry. If necessary, clean prior with GLOUROS Cleaner No.1806 to remove any greying, mould or algae build up. If an old varnish exists it may be necessary to sand this off.

Do not use or store oils below 12 °.

YOU WILL NEED

Mop/applicator or roller

Paint brush for edges and grooves

Cloths or clean rags Paint tray (optional)

Oil Air tight sealed container for used rags/pads etc. * see safety information

APPLICATION

1 st Coat stir well. Using the paintbrush work the oil carefully along edges, and between the boards. Then apply in the direction of the wood grain. Be careful not to splash the oil as this could leave permanent marks on stones, walls or skirting boards.

After 10 minutes saturation time (depending on temperature and humidity), remove or spread out any excess oil from the timber. If necessary, walk over the oil to the starting point and commence working from there. Move backwards over the area walked, this will remove any footprints and will not mark the deck surface. Dry around edges with clean absorbent rags ensuring that the timber is touch dry.

2 nd Coat (Next Day- if humid day 3) Stir well. There is no need for sanding in-between coats. Repeat steps for 1st coat applying the oil thinly. Less oil will be used than for previous coat. Work in or remove any excess oil after approximately 10 minutes.

If left too long or is in direct sun, it may start to become tacky. If this happens, work in some more oil to dissolve it again and wipe off. Leave overnight.

Decant any unused oil into a smaller container for future use.



Application of Livos oils to timber decking (cont'd)

The finished decking must not have a thick layer of oil on top of. The oils impregnate the timber and seal from within, and not by creating a thick layer on top of the timber.

CARE & MAINTENANCE AND REJUVENATION

Wash occasionally with a PH neutral cleaner such as Livos Trena #556

Rejuvenation Ensure surface is clean and dry. Apply 1 thin coat of the original oil used. If the timber has been left for too long without rejuvenating and it has started to "grey" wash with GLOUROS Cleaner # 1806 and apply 2 coats of Alis 579.

. * SAFETY INFORMATION

Always be sure to store cleaning rags and applicators that are still wet or even slightly moist with Livos oils in an airtight metal container or in water, as there is a danger of spontaneous combustion caused by the linseed oil in the product.

The product alone will not undergo spontaneous combustion.

Do not use or store oil below 12 °

"Our information is given in good faith and is based on results obtained from experience and tests. However, as the workmanship is beyond our control, all recommendations and suggestions are made without guarantee." To download this information or for further information please read Technical Data Sheet on our website or contact us

The information set out in respect to the preparation and application of LIVOS oils and safety information is based on many years of experience applying these oils on various timbers in commercial and domestic locations. If these instructions and suggestions are followed you should have a quality finish. However no responsibility can be accepted where we have not supervised or applied the oils. By following some recommendations, a life of low maintenance is prolonged.