

# DUPLEX

Double-sided adhesive tape



## Technical Data:

Characteristics	Value
release paper	siliconized paper made from PE
temperature resistance	long term -40°C to +90°C
application temperature	from -10°C
colour	transparent
storage	cool and dry

## Applications:

### Outside:

Used to join overlaps between sarking membrane, roof lining membrane and wall lining membrane as well as roofing underlay and airtightness membrane on hard substrates and provide protection against humidity. The airtight bonds meet the requirements of DIN 4108-7, SIA 180 and ÖNorm B8110-2.

### Inside:

For attaching vapour check and airtightness membrane to metal sections and for joints to windows, for example.

## Delivery Form:

Mat. No.	EAN	Length	Width	PU	PU/Pallet
10123	4026639016591	20 m	2.5 cm	30	63
10686	4026639016218	80 m	2.5 cm	10	Big pack * 75

\* only available by the box!

## Surfaces:

Before bonding, the substrate surface should be swept clean with a broom or wiped with a cloth. Bonding to frozen surfaces is not possible. The substrate material must be free of water-repellent substances (e.g. grease or silicone). The substrate must offer sufficient load-bearing capacity. A permanent bond is achieved on all pro clima indoor membranes (vapour check and airtightness membrane as well as trickle protection membrane) and PE, PA, PP and aluminium foil used to create an airtight seal. Bonding and joints are possible with planed and painted wood, high density plastic and metal (e.g. pipes, windows etc.), hardboard (chipboard, OSB and veneer plywood).

The best results for the safety of the structure can be achieved on high-quality substrates. The applicator is responsible for checking the suitability of the substrate. Adhesion tests are recommended.

## Features/advantages:

- ✓ Durable leak-proof bonding, inside and out
- ✓ For airtight bonds in accordance with DIN 4108-7, SIA 180 and ÖNorm B8110-2
- ✓ Especially easy to use with the DUPLEX hand dispenser (for 20 m rolls) – unroll, press on and tear off in a single operation.

The information provided here is based on practical experience and the current state of knowledge. We reserve the right to make changes to the recommendations given or to make alterations due to technical developments and associated improvements in the quality of our products. We would be happy to inform you of the current technical state of the art at the time you use our products.



sales: 01793 847 444  
email: [info@ecomerchant.co.uk](mailto:info@ecomerchant.co.uk)  
web: [www.ecomerchant.co.uk](http://www.ecomerchant.co.uk)

