

ECO COLL Natural latex-glue



Technical Data:

Characteristics	Value
material	natural latex, tree gum, casein talcum powder, cellulose, water
temperature resistance	long term up to +40 °C
application temperature	from -10 °C
storage temperature	frost free
storage environment	cool and dry

Applications:

For creating permanently airtight joints between vapour check and airtightness membrane made of building paper (e.g. pro clima DB+), both for bonding the overlaps between sheets as well as bonding joints on suitable substrates in accordance with our application recommendations. The bonds meet the requirements of DIN 4108-7, SIA 180 and OeNorm B8110-2.

Delivery Form:

Mat. No.	EAN	Delivery form	Content	Coverage	PU	PU/Pallet
10104	4026639016201	Cartridge	310 ml	bead 5 mm ~15 m bead 8 mm ~6 m	20	60
10105	4026639016034	Tube	600 ml	bead 5 mm ~30 m bead 8 mm ~12 m	12	60

Surfaces:

Before bonding, the substrate surface should be swept clean with a broom or wiped with a cloth. Mineral substrates (such as plaster or concrete) may be slightly damp. Bonding to frozen surfaces is not possible. The substrate material must be free of water-repellent substances (e.g. grease or silicone). The substrate must offer sufficient load-bearing capacity. It may be necessary to use a mechanical support (pressure lath), for example on sanding substrates.

A permanent bond is achieved on pro clima vapour check papers. Joints are possible on mineral substrates (such as plaster or concrete), to planed and painted wood, high density plastic and non-rusting metal (e.g. pipes, windows etc.), and hardboard (chipboard, OSB, veneer plywood and MDF board). The applicator is responsible for checking the suitability of the substrate. Adhesion tests are recommended.

Features/advantages:

- ✓ Wetting ability
- ✓ Ecologically friendly glue for making building paper durably airtight
- ✓ No pressure lath required
- ✓ Can be used on slightly damp surfaces

The information provided here is based on practical experience and the current state of knowledge. We reserve the right to make changes to the recommendations given or to make alterations due to technical developments and associated improvements in the quality of our products. We would be happy to inform you of the current technical state of the art at the time you use our products.



sales: 01793 847 444
email: info@ecomerchant.co.uk
web: www.ecomerchant.co.uk

