

TESCON PRIMER RP

Solvent-free primer, no drying required



Technical data

Substance		
Material	acrylic copolymer, solvent-free	
Attribute	Regulation	Value
Colour		white
Application temperature		-10 °C to +45 °C
Temperature resistance		permanent -40 °C to +90 °C
Storage		protect from frost, cool and dry

Area of application

Adhesive primer for wood, fibreboard, masonry, roof, wall and floor boards for priming the substrate for subsequent bonding with pro clima TESCON No.1, TESCON VANA or TESCON PROFIL adhesive tape.

Consumption figures			
Delivery form	Content	Adhesive tape width	Coverage
Tin	0.75 l	60 mm	~ 60 m
		75 mm	~ 45 m
		150 mm	~ 22 m
Tin	2.5 l	60 mm	~ 185 m
		75 mm	~ 150 m
		150 mm	~ 75 m
Dispenser bottle	1 l	60 mm	~ 75 m
		75 mm	~ 60 m
		150 mm	~ 30 m

The quantity used may vary depending on the substrate and application method.

Forms of delivery

Itemnumber	GTIN	Contents	Trade unit	Packing units	Weight
11427	4026639114273	0.75 l	cans	6	1 kg
11430	4026639114303	2.5 l	cans	4	3 kg
11449	4026639114495	1 l	BTLS	6	1.13 kg

Advantages

- ✓ No drying required - adhesive can be applied straight to the damp primer on absorbent substrates
- ✓ Deep penetration of the primer, excellent hardening
- ✓ Application even on damp substrate
- ✓ Can also be used in the event of frost
- ✓ Can be used with any pro clima adhesive tape
- ✓ Solvent free

The information provided here is based on practical experience and the current state of knowledge. We reserve the right to make changes to the recommended designs and processing or to make alterations due to technical developments and associated improvements in the quality of our products. We would be happy to inform you of the current technical state of the art at the time you use our products.



Substrates

Before priming, the substrate surface should be swept clean with a broom or cleaned. The primer cannot be used on frozen or saturated substrates. The substrate material must be free of water-repellent substances (e.g. grease or silicone).

The primer can be used to treat all mineral substrates such as plaster or concrete. It can also be used to harden porous materials such as wood fibre sub-roof panels, for example.

In addition to this, it can be used to prepare (old) wood substrates for bonding.

Permeable, absorbent substrates (e.g. wood fibre sub-roof panels) may be slightly damp. The adhesive tape being used can be stuck straight on to the damp primer.

General conditions

Shake or stir the can well before use. One litre of primer can be used to treat an area of about 4.5 m².

For extra quick work: no drying is required for absorbent substrates. Bonding can take place on the damp primer.

For particularly quick and easy application insert the 1-litre dispenser bottle in to the new TENAPP application tool.

Advantages: Application and distribution in just one step, using just one hand and no contamination of the primer in the container.

The information provided here is based on practical experience and the current state of knowledge. We reserve the right to make changes to the recommended designs and processing or to make alterations due to technical developments and associated improvements in the quality of our products. We would be happy to inform you of the current technical state of the art at the time you use our products.



sales: 01793 847 444
email: info@ecomerchant.co.uk
web: www.ecomerchant.co.uk

