



produkt by pro clima
MDLL baufkologische Produkte GmbH
e-8723 Schwetzingen, Germany

(D) (A) (CH) (USA) (CAN) (RUS) (S)



pro clima

EXTOSEAL[®] MAGOV

Highly flexible airtightness adhesive sealing tape

Highly elastic adhesive tape for airtight seals, e.g. in the skirting area or for penetrations such as pipes, installation parts etc.

- ✓ Perfect for sealing penetrations as a result of its particularly strong butyl rubber layer and elastic carrier film with low restoring forces
- ✓ Protects even when highly stretched
- ✓ Protects structural elements from water ingress: watertight and blocks rising damp
- ✓ Creates a secure bond: butyl rubber penetrates deep into the substrate
- ✓ Bonds to mineral substrates



www.proclima.com

... and the insulation
is perfect



pro clima **EXTOSEAL**® **MAGOV**

Highly flexible airtightness adhesive sealing tape



Technical data:

Characteristic	Regulation	Value
Backing		Elastic PE carrier film
Material		Butyl rubber
Separation layer		Silicone-coated PE film
Colour		Butyl rubber grey, film: blue
Mass per unit area	DIN EN 1849-2	About 3.7 kg/m ²
Thickness	DIN EN 1849-2	About 2.0 mm
Temperature resistance		Permanently -20 °C/-4 °F to +80 °C/176 °F
Application temperature		From +5 °C/41 °F to 35 °C/95 °F, frost-free nights
Storage		Cool and dry

Delivery Form:

Art.-Nr.	EAN	length	width	PU	PU/Pal.	weight (kg/PU)
14343	4026639143433	10 m	6 cm	5	60	11.5 kg
14344	4026639143440	10 m	10 cm	3	60	11.5 kg

Measure out the tape



Roll out the tape to the required length and cut to size.

Remove the first release film



Fold the tape in the middle and remove the first release paper.

Tape onto tube



Place the tape on the tube and tape it around the tube gradually. Ensure sufficient coating of the ends.

Tape onto surface



Remove the second release paper completely. Gradually fold the tape onto the surface and piece by piece tape it all around.

Press on firmly



Afterwards, press bonding firmly all around. Ensure there is sufficient back-pressure. The pressing aid pro clima PRESSFIX is particularly efficient and protects your hands.

Outdoor applications too



EXTOSEAL MAGOV also provides secure joining of penetrations outdoors, e.g. through wall lining membranes, sarking membrane and roof lining membrane.

ecomerchant
ETHICAL · HEALTHY · SUSTAINABLE

sales: 01793 847 444

email: info@ecomerchant.co.uk

web: www.ecomerchant.co.uk

MOLL
bauökologische Produkte GmbH
Rheintalstraße 35 - 43
D-68723 Schwetzingen
Germany
☎ +49 (0) 62 02 - 27 82.0
☎ +49 (0) 62 02 - 27 82.21
info@proclima.com

www.proclima.com

