




# TESCON® SPRIMER

## Sprayable primer

Wash primer for wood, wood-fibre boards, masonry, roofs, walls and ground slabs for subsequent adhesion with pro clima adhesive tapes such as TESCO VANA, TESCO PROFECT and the EXTONSEAL range.

### Advantages

- ✓ Easy to apply - spray on directly from the can, no contamination of the primer in its container
- ✓ Secure bonds: penetrates deep and strengthens dusty subsurfaces or subsurfaces with insufficient load-bearing capacity
- ✓ Saves time: adhesive tapes can be stuck to absorbent subsurfaces with no drying time
- ✓ Flexible use: use on dry and slightly moist subsurfaces
- ✓ At any time of the year: can also be applied during frosty conditions



... and the insulation  
is perfect



# TESCON® SPRIMER

Sprayable primer



## Technical data

Substance	
Material	Synthetic rubber
Attribute	Value
Colour	translucent
Application temperature	23 °F to 104 °F ; -5 °C to +40 °C
Temperature resistance	permanent 23 °F to ~195 °F, short-term up to 212 °F (1 h); °C: -5 to ~90; 100
Storage	protect from frost, cool and dry

## Forms of delivery

Art. no.	GTIN	Content	Adhesive tape width	Coverage	PU	PU/pallet
1AR01114	4026639211149	13.5 oz (400 ml)	2 3/8" (60 mm)	~22 yd (20 m)	12	84
			3" (75 mm)	~18.5 yd (17 m)		
			6" (150 mm)	~10 yd (9 m)		
1AR01050	4026639210500	25.4 oz (750 ml)	2 3/8" (60 mm)	~41 yd (38 m)	6	56
			3" (75 mm)	~34 yd (31 m)		
			6" (150 mm)	~18.5 yd (17 m)		

## Application Guide



### 1 Preparing the subsurface

Brush off or wipe down the subsurface, if necessary.



### 2 Preparing the can of primer

Shake the can vigorously for at least 20 seconds.



### 3 Applying the primer

Spray TESCO SPRIMER from a distance of approx. 20 cm to the surface to form a seamless coating.



### 4 Turning the jet direction

The spray jet can be adjusted in the vertical or horizontal directions to suit the application situation.



### 5 Sticking

The pro clima adhesive tapes TESCO or CONTEGA, for example, can be stuck onto surfaces treated with primer without any waiting period.



### 6 Final adhesive strength

The adhesive joint achieves its high final level of strength once the primer has dried fully.

Distributed by :



sales: 01793 847 444  
 email: info@ecomerchant.co.uk  
 web: www.ecomerchant.co.uk

