

# Declaration of Performance




No. DoP672010

- Product type:**  
General purpose mortar (GP)
- Constructions product identification:**  
SkamoWall Smooth Plaster
- Intended use of construction product:**  
Intended for use on walls, ceilings and partitions, in particular as mineral filler used for silicate-limestone panel
- The manufacturer's name and address:**  
Skamol A/S  
Østergade 58-60  
DK-7900 Nykøbing Mors
- The authorized representative's name and address:**  
Not relevant
- Systems of assessment and verification of constancy of the performance (AVCP):**  
AVCP-System 4
- Notified body tasks, if relevant:**  
Not relevant
- Declared performance:**

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Class F	EN 998-1:2010, IDT
Dry bulk density [ $\text{kg/m}^3$ ]	$\leq 1400$	EN 998-1:2010, IDT
Compressive strength	CS II	EN 998-1:2010, IDT
Water absorption	Class W0	EN 998-1:2010, IDT
Water vapor permeability, $\mu$	$\leq 15$	EN 998-1:2010, IDT
Adhesion	$\geq 0,08 \text{ N/mm}^2$ Fracture pattern B	EN 998-1:2010, IDT
Thermal conductivity, $\lambda_{10,\text{dry}}$	$\leq 0.45 \text{ W/mK}$ (average tabular value, P=50%)	EN 998-1:2010, IDT
Dangerous substances	See safety data sheet	EN 998-1:2010, IDT

- The performance of the construction product referred to in point 1 and 2, are consistent with the declared performance in point 8.**  
This declaration of performance is issued under the regulation (EU) No.305/2011 and under the sole responsibility of the manufacturer, listed in point 4. Signed for and on behalf of the production by:

  
Susanna Knudsen, Quality Manager, Skamol A/S

Nykøbing Mors 06-09-2017, rev 01